Secondary Vertex Finding w/ RAVE

Sanghoon Lim


Multi-vertex finding with Rave


- It's implemented in the Genfit module (done by Haiwang)
 - Put these in the G4_Svtx.C macro (or other silicon tracker macros)

```
PHG4TrackKalmanFitter *kalman = new PHG4TrackKalmanFitter(); kalman->set_do_eval(true); kalman->set_vertexing_method("tkf-smoothing:1"); se->registerSubsystem(kalman);
```


- Multi-vertex option
 - 1) "tkf": trimmed Kalman filter (remove tracks incompatible with the vertex)
 - 2) "avr": adaptive filter (use weight function)
 - →checking initial parameters can be adjusted in the GFRave
 - 3) "mvf-ini:(finder:avr)": simultaneous fit with 'n' seeds
 - →checking a certain track is used in multiple vertices with different weights
- "SvtxVertexMapRefit" node will be created


- udsg jets (PhaseSpace:pTHatMin = 25 GeV), 7 layers MAPS
 - put all reconstructed tracks into the vertex finder, generated (0,0,0)
 will test tracks within a certain area (jet cone)







- udsg jets (PhaseSpace:pTHatMin = 25 GeV), 7 layers MAPS
 - put all reconstructed tracks into the vertex finder, generated (0,0,0)
 will test tracks within a certain area (jet cone)






- Testing with simple case (fixed decay mode with HardQCD:bbbar)
 - put all reconstructed tracks into the vertex finder, generated (0,0,0)






- Testing with simple case (fixed decay mode with HardQCD:bbbar)
 - put all reconstructed tracks into the vertex finder, generated (0,0,0)



associated tracks in ~87% of secondary vertices from 1 mother particle (source)

Comparison between udsg / c / b (~5k events for each)



Next...

- Rave in sPHENIX software
 - checking interfaces in GFRave for setting parameters
- Performance check
 - vertex finding with tracks in a jet
 - comparison between three methods
 - secondary vertex mass?